

# WE-EF Core Products 2017

**2 WEEK QUICK SHIPMENT FOR ALL PRODUCTS LISTED<sup>1</sup> (LIMITED QUANTITY)**

**we-ef**



## ETC110\* / 120 / 130 / 140 / 330

Offset gimbal optics with up to 30° tilt and 360° rotation. Rated to 5 metric Tons /11,000 pounds. Suitable for Drive over. Water white glass for greater optical efficacy. Choice of 5 field changeable lenses with a host of optical accessories. IP67. Universal power 120-277V. Installation Blockout included. (Also available with ASC coating)

\*ETC110 is not a gimbal

**SAME DAY SHIPMENT OF BLOCKOUTS<sup>2</sup>**

ETC110	3W	Ø: 9.8"	307 to 313 lm
ETC120-GB	6W	Ø: 9.8"	509 to 515 lm
ETC130-GB	18W	Ø: 9.8"	1676 to 1932 lm
ETC140-GB	24W	Ø: 11.8"	2529 to 3014 lm
ETC330-GB	12W	Ø: 9.8"	1220 to 1406 lm

**OPTICS**  
Wide (50°)  
Medium (30°)  
Very Narrow (12°)  
Very Narrow Sharp (10°)  
Wall Wash (A20°)



## ETC320 FS / 330 FS / 340 FS

FACTORY SEALED – NO IN-FIELD OPENING DURING INSTALLATION fixed optics. Rated to 5 metric tons /11,000 pounds. Suitable for drive over. Water white glass for greater optical efficacy. Choice of 5 lenses with a host of optical accessories. IP67. UL wet listed. Supplied with an installation Blockout as standard. Luminaires are never opened during installation. (Also available with ASC coating)

**SAME DAY SHIPMENT OF BLOCKOUTS<sup>2</sup>**

ETC320 FS	12W	Ø: 6.3"	1156 to 1378 lm
ETC330 FS	24W	Ø: 9.8"	2231 to 2572 lm
ETC340 FS	36W	Ø: 11.8"	3475 to 4141 lm

**OPTICS**  
Wide (50°)  
Medium (30°)  
Very Narrow (12°)  
Very Narrow Sharp (10°)  
Wall Wash (A20°)

## FLC121 / 131 / 141

High performance floodlight projector. Superior light control. Choice of 5 field changeable lenses with a host of optical accessories. Wet listed IP66.

**FLC122 COMING SOON!**



FLC121	12W	Ø: 4.4"	1142 to 1366 lm
FLC122	12W	Ø: 4.4"	1142 to 1366 lm
FLC131	24W	Ø: 6.1"	2297 to 2610 lm
FLC141	48W	Ø: 7.6"	4570 to 5464 lm

**OPTICS**  
Wide (50°)  
Medium (32°)  
Very Narrow (14°)  
Very Narrow Sharp (10°)  
Wall Wash (A20°)

## FLD111

A high performance floodlight projector wet listed IP66. 5CE superior corrosion protection including PCS hardware.



FLD111	6W	Ø: 5.3"	590 to 594 lm
--------	----	---------	---------------

**OPTICS**  
Medium (42°)  
Very Narrow (14°)  
Very Narrow Sharp (10°)  
Wall Wash (A20°)

## DOC 220

Wet listed IP66 exterior rated high performance down light. Suitable for under canopies, eaves of buildings and in particularly environments that are exposed to high levels of salt, wind and moisture. (Also available in Stainless Steel)



DOC220	24W	Ø: 6.0"	2297 to 2610 lm
--------	-----	---------	-----------------

**OPTICS**  
Wide (50°)  
Medium (30°)  
Very Narrow (12°)  
Very Narrow Sharp (10°)  
Wall Wash (A20°)

## DAC220

Wet listed IP65 exterior rated high performance down light. Suitable for under canopies, eaves of buildings and in particularly environments that are exposed to high levels of salt, wind and moisture.



DAC220	24W	Ø: 6.0"	2297 to 2610 lm
--------	-----	---------	-----------------

**OPTICS**  
Wide (50°)  
Medium (30°)  
Very Narrow (12°)  
Very Narrow Sharp (10°)  
Wall Wash (A20°)

# WE-EF Core Products 2017

**2 WEEK QUICK SHIPMENT FOR ALL PRODUCTS LISTED<sup>1</sup> (LIMITED QUANTITY)**

**we-ef**



## OLV330 / 334 / 340 / 344

Wet listed IP65. Surface mounted wallwasher. Suitable for installation over 4" recessed junction box in uplight or downlight position.

**COMING SOON!**

OLV330	12W / 18W	1910 to 1960 lm
OLV334	12W / 24W	1390 to 1960 lm
OLV340	24W / 36W	3853 to 4105 lm
OLV344	24W / 48W	2688 to 4462 lm

**OPTICS**  
S70 – Type II Short  
A60 – Type IV Short  
R65 – Type IV Medium



## QRI354 / 374

Wet listed IP55. Recessed LED wall luminaire. Shielded light source with asymmetric forward throw. Suitable for installation in cavity wall construction or concrete pour construction using optional installation blockout.

**COMING SOON!**

QRI354	6W	515 lm
QRI374	14W	894 lm



## VFL520 / 530 / 540

High performance LED site luminaires with some of the best optics available on the market. Optics optimized for pathways (P65/S70/S60), Roads (S65), Parking Lots (R65) and collection areas (A60). Designed for easy upgradability and maintenance.

**POLE NOT INCLUDED IN QUICK SHIP**

VFL520	12W / 24W	2500 to 2723 lm
VFL530	12W / 48W	1411 to 5297 lm
VFL540	24W / 84W	2821 to 9390 lm

**OPTICS:**  
S70 – Type II Short  
P65 – Type II Medium  
S60 – Type III Short  
S65 – Type III Medium  
A60 – Type IV Short  
R65 – Type IV Medium



## QLS410-1 / 410-2 / 420-1 / 420-2

Wet Listed, IP66, Surface mounted LED wall luminaire. Suitable for installation over 4" recessed junction box. 5C corrosion protection.

QLS410-1	6W	557 to 570 lm
QLS410-2	12W	1114 to 1192 lm
QLS420-1	12W	1114 to 1140 lm
QLS420-2	24W	2229 to 2384 lm

## AVAILABLE FOR 1 WEEK QUICK SHIPMENT

Available in Standard Finish Only



## LED STEPLIGHTS

Recessed marine grade step lights. IP55. UL Listed. Blockout available for concrete pour applications. (STO200 and STG200 also available in Stainless Steel)

## SAME DAY SHIPMENT OF BLOCKOUTS<sup>2</sup>



STN200	4W / 6W	3.6" X 8.0" to 3.6" X 9.8"
STI200	6W / 9W	3.6" X 9.8" to 5.3" X 16.7"
STL200	4W / 6W	3.6" X 8.0" to 3.6" X 9.8"
STG200	4W / 6W	3.6" X 8.0" to 3.6" X 9.8"
STO200	4W / 9W	3.6" X 8.0" to 5.3" X 16.7"

Core products list as of March 1, 2017. List is subject to change and will be redistributed if changes occur.

<sup>1</sup> Product quantity and availability subject to demand

<sup>2</sup> Same-Day Blockout shipment if ordered by 2PM EST