



FORMULA 922

URETHANE ADHESIVE REMOVER

LOW ODOR/HIGH FLASPOINT/REMOVES CURED ADHESIVES

Product Description

Sentinel 922 Urethane adhesive Remover is a low-odor, biodegradable product designed to remove wet and recently cured urethane adhesives from pre-finished wood flooring, as well as facilitating the removal of damaged glued-down floors.

Application Information (Always follow product label instructions for best results)

DIRECTIONS:

REMOVING URETHANE ADHESIVES

Step 1: Protect walls, drains, cracks and other flooring with an absorbent. Wet the entire adhesive surface with 922, using a sprayer or mop. Allow 922 to soak and penetrate for 30-60 minutes, depending on the thickness of the adhesive.

Step 2: Scrape the bulk of the softened adhesive from the surface with a razor floor scraper.

Step 3: Reapply 922 and agitate using brooms or stripper pads. Liquefied adhesive can be absorbed using kitty litter (absorbent) and then removed.

Step 4: Wash and rinse floor thoroughly with Sentinel 810 and water to ensure a clean surface. Allow to dry thoroughly.

REMOVAL OF GLUED DOWN WOOD FLOORING :

Step 1: Cut the wood surface using a circular saw into 6" to 8" squares. Set the saw deep enough to cut through the flooring down to the subfloor.

Step 2: Vacuum all sawdust from the floor and cut lines.

Step 3: Apply liberal amounts of 922 to the cut lines using a squeegee or mop. Allow 922 to soak and penetrate under the wood for 4-8 hours.

Step 4: Using a spade or similar tool, pry up old wood flooring. Squares should be intact and easy to remove. Once flooring is removed, follow directions for removing adhesive from subfloor.

COVERAGE:

Expect coverage rates of 100-200 sq. feet per gallon on adhesive removal and 75 sq. feet per gallon on flooring removal.

V.O.C. CONTENT:

This Floor or Wall Covering Adhesive Remover contains less than 5% V.O.C. content by weight, in accordance with the requirements set forth by the California Air Resource Board (CARB) and Ozone Transport Commission (OTC), effective 1-1-2009.

WARRANTY NOTICE:

Seller makes no warranty, expressed or implied, nor accepts any responsibility for any direct or consequential damages beyond purchase price, because seller cannot control users handling and use or effect of that use.

HAZARD RATING: HMIS
HEALTH 1
FLAMMABILITY 1
REACTIVITY 0
PERSONAL PROTECTION H

PROPERTIES

Physical state: Liquid

Appearance: Clear

Color: None to amber

Odor: Mild Musty Odor

pH: Not Applicable

Boiling Point: 470° F.

Flash Point: 200° F.

Vapor Pressure:<0.2 mm Hg@68° F.

VOC Content: <500 g/l*

* When determining VOC content in accordance with the requirements set forth by the Ozone Transport Commission (OTC), effective 01-01-2009



922 URETHANE ADHESIVE REMOVER

V.O.C. COMPLIANT

SENTINEL 922 URETHANE ADHESIVE REMOVER

Sentinel 922 Urethane Adhesive Remover is a low-odor, biodegradable product designed to remove wet and recently cured urethane from pre-finished wood flooring, as well as facilitating the removal of damaged glued-down floors.



Low Odor / High Flashpoint / Removes Cured Adhesives

800-373-0633 or www.senpro.com

Sentinel Products, Inc. / 8901 Wyoming Avenue North, Brooklyn Park, MN 55445