

Janome Club

Thursday 9th 10am-12pm



A Closet Hanger Safe

You will need:

- Sewing machine, cord, foot control,
- Regular sewing foot and a zipper foot.
- Walking or Even Feed foot; or engage your machine's built-in fabric feeding system, such as the AccuFeed™ Flex feeding system on many of our Janome machines
- Thread to match your fabric

Supplies for ONE hanger safe:

- 1 1/4 yard of fabric (or 1 yd. 54" + wide decorator weight fabric) for the body of the safe, the back pockets, and the zipper end tabs; we used Petal Dot in Pink and Petal Dot in Red
- 3/4 yard of coordinating (or 3/4 Yd. 54" + wide decorator weight) fabric for the front pocket and straps; The straps require just FOUR 2" x 13" strips
- 1 yard of 45"+ wide mid-weight fusible interfacing; --- Pellon 809 Décor Bond
- 1 yard of 20"+ wide lightweight fusible interfacing; --- Pellon 950F Shir-Tailor
- TWO 16" standard zippers (not metal)
- 1/2 yard 3/8" wide ribbon for the front pocket closure
- 1/2 yard of 1/8" wide ribbon for the zipper pulls
- Scissors or rotary cutter and mat*
- See-through ruler*
- Straight pins*
- Seam gauge*
- Seam ripper*