

Specification Sheet

Part Number: T30R9M4



Standard Cable Tie, 5.8" Long, UL Rated, 30lb Tensile Strength, PA66, Natural, 1000/pkg

Article Number	111-03047
Type	T30R
Color	Natural (NA)
Features & Benefits	• Inside serrations allow for strong grip on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
Quantity Per	bag

Product Description

T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description	Standard Cable Tie, 5.8" Long, UL Rated, 30lb Tensile Strength, PA66, Natural, 1000/pkg
Global Part Name	T30R-PA66-NA
Minimum Tensile Strength (Imperial)	30.0
Minimum Tensile Strength (Metric)	135.0
Length L (Imperial)	5.8
Length L (Metric)	148.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.14
Width W (Metric)	3.6
Bundle Diameter Min (Imperial)	0.06
Bundle Diameter Min (Metric)	1.5
Bundle Diameter Max (Imperial)	1.38
Bundle Diameter Max (Metric)	35.0

Thickness T (Metric)	1.1
Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
US MIL SPEC	MS3367-5-9
SAE-AS81531	
Flammability	
UL 94 V2	Halogen free
Yes	Operating Temperature (Metric)
-40°F to +185°F (-40°C to +85°C)	ROHS Complaint
Yes	Certification/Specification WEB
CAGE Code 53421 DNV GL IEC 62275:2006 Bundesamt für Wehrtechnik VG 95387 Part 4 Edition: 2008-12	UL Recognized (US)
Yes	UL Listed (US and Canada)
Yes	UL Recognized (US and Canada)
Yes	
Package Quantity(Imperial)	1000
Package Quantity (Metric)	1000

Customs Number	3926909987
Weight (Metric)	0.7