

Specification Sheet

Part Number: 151-01108



Connector Clip w/Oval Fir Tree, 0.6 - 6.0 mm Panel Thickness, Hole Dia. 6.2–13.0mm, PA66HIRHS, Black, 5000/ctn

Article Number	151-01108
Type	CCOVAL2
Color	Black (BK)
Features & Benefits	•Head design contains clamping rails to provide full circumferential compression around bundles. •Bent tail allows for quick insertion into head.
Quantity Per	carton

Product Description	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
---------------------	---

Short Description	Connector Clip w/Oval Fir Tree, 0.6 - 6.0 mm Panel Thickness, Hole Dia. 6.2–13.0mm, PA66HIRHS, Black, 5000/ctn
Global Part Name	CCOVAL2-PA66HIRHS-BK
Length L (Imperial)	1.14
Length L (Metric)	28.97
Fixation Method	Fir Tree for oval holes
Width W (Imperial)	0.69
Width W (Metric)	17.63
Height H (Imperial)	0.80
Height H (Metric)	20.35
Panel Thickness Min(Imperial)	0.02
Panel Thickness Max(Imperial)	0.24
Panel Thickness Min (Metric)	0.6
Panel Thickness Max (Metric)	6.0
Mounting Hole Diameter D (Imperial)	0.24 x 0.48 " 0.25 x 0.50 " 0.25 x 0.50 " 0.27 x 0.47
Mounting Hole Diameter D (Metric)	7.0 x 12.0 mm 6.2 x 12.2 mm 6.5 x 13.0 mm 6.5 x 12.5 mm
Mounting Hole Diameter D Min (Imperial)	0.24

Mounting Hole Diameter D Max (Imperial)	0.51
Mounting Hole Diameter D Max (Metric)	13.0
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Operating Temperature (Metric)	-40°F to +230°F (-40°C to +110°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Package Quantity(Imperial)	5000
Package Quantity (Metric)	5000
Customs Number	3926909987
Content Unit(BMEcat)	pcs.