

Gates & Barriers

Fall Protection Statistics You Need to Know



Fall Protection is No. 1 on OSHA's list of most-violated guidelines



On average, one loading dock sees 100,000 crossings per year



Approx. \$5.3 billion or 8.7% of disability claims are the result of a fall to a lower level



There are approx. 62,000 forklift accidents per year resulting in approx. 35,000 serious injuries.



Dock Impact Barrier™

APS Resource Gates & Barriers Product List

Dock Impact Barrier™

-An APS Resource premier product, the Dock Impact Barrier is built to withstand a 10,000 lb gross load at an impact speed of 4 mph. The gate also boasts a 42" inch maximum height, meeting OSHA standards. It is also capable of stopping 200 lbs from any direction. The gate is manually raised using a foot latch with a gas spring assist that makes for easy operation. Fits doors 6' - 10'

Dock Impact Barrier - LC™

-The Dock Impact Barrier-LC matches the rigorous standards of the Dock Impact Barrier while reducing overhead clearance requirements by 30". Its resiliency is proven by its capability to stop a 10,000 lb gross load impact at 4 mph. The LC also passes the OSHA test with a 42" height and is safeguarded against 200 lb force from any direction. The manually operated gate fits doors 8' - 10'.

Work Safe Gate™

-Provides excellent visual protection for personnel. Like the gates previously mentioned, the Work Safe Gate has an OSHA-qualified top rail of 42" high that can stop 200 lbs of force from any direction. This product is easily operated with no electrical requirements. It's enhanced with the addition of a padlock so it can be locked out. Fits doors 6' - 10'



APS Resource
Your Aftermarket Solution

APS Resource
262-518-1000
6219 W. Eastwood Ct.
Mequon, WI 53092



MODERN
Dock & Door Service®
2501 Durham Road
Bristol, PA 19007
1-800-866-3376
moderngroup.com/dockservice