




**MULTI LUMEN  
SELECTOR**

**EASY 5 COLORS  
SELECCTOR**  
2700K • 3000K • 3500K • 4000K • 5000K



NOMINAL LUMENS	DELIVERED LUMENS	WATTAGE
500	605	9W
650	720	10W
800	940	12W

Based on 4000K, 90+ CRI. Actual wattage may vary +/- 5%

**INSTALLATION**

Cut hole in ceiling. Insert luminaire into opening by squeezing spring clips on both sides of luminaire. The width in ceiling needed for the driver to fit is 3".

You **MUST** seal all gaps between the ceiling and fixture with weatherproof silicone sealant. This deters moisture and water from damaging fixtures and other mechanical ceiling elements.

**FEATURES**

4" round multi-CCT LED "Slim Disk" engineered for new construction, remodel, or retrofit to accommodate insulated or dropped ceilings. Easily access field-adjustable 5-Color SeleCCTor switch by lowering the luminaire from the opening. Recessed housing not required, especially with limited plenum applications. Remote driver allows easy installation and maintenance. Small aperture and shallow depth are ideal for unlimited applications.

LUMENS	500/650/800
CCT	27K/30K/35K/40K/50K
CRI	90+
COLOR QUALITY	3-Step MacAdam Ellipse
CONSTRUCTION	Aluminum die-cast body and trim
TRIM OPTION	Round Flat Lens
TRIM COLORS	WH (White), BK (Black), BZ ( Bronze), SN (Satin Nickel), CP (Copper), CH ( Chrome)
DIMMING	DIMTR (Triac), DIM10 (0-10V)
EMERGENCY	16W high voltage inverter ( remote)
LIFETIME	L70 at 50,000 Hours
PHOTOMETRIC TESTS	In Accordance with IES LM79-08, LM80 and TM-30, TM-21

- IC-rated and Air-Tight ready and may be in direct contact with insulation.
- Can be installed in shallow plenum spaces.
- May be installed in drywall or suspended ceilings.
- Flicker-free 120V forward-phase Triac dimming down to 5%.
- Even illumination achieved with patent-pending optics and edge-lit LED technology.
- Ideal where ceiling or top access is unavailable.
- Operating temperature range -15°C. to 35°C.



**SLIM TRIM**



**TRIM RINGS**



**RL475-RT-BK**  
(Black)



**RL475-RT-BZ**  
(Bronze)



**RL475-RT-CH**  
(Chrome)



**RL475-RT-CP**  
(Copper)



**RL475-RT-SN**  
(Satin Nickel)

**RL475-RT-BZ**

**ACCESSORIES**




**RL-ACC-SLIM-1-10F**  
10-ft long extension




**RL-ACC-SLIM-1-20F**  
20-ft long extension




**RL-UNV-4/5/6**  
For use with: 4", 5", 6"



**AL-ACC-SLIM-4-F-ROUGHPLATE**  
For 4" downlight



**RL-ACC-SLIM-4-ROUGHPLATE**  
Rough-in plate for use with 4" downlights



**RL-ACC-SLIM-1-10F**

EXAMPLE:  
REL475-500L/650L/800L-DIMTR/120-DIM10/  
MVOLT-27K/30K/35K/40K/50K-90-WH

TYPE	LUMEN	CCT	CRI	FINISH
REL475	500L/650L/800L-DIMTR/120-DIM10/MVOLT	27K/30K/35K/40K/50K	90+	WH - White

ACCESSORIES
<input type="checkbox"/> RL475-RT-BZ - Bronze <input type="checkbox"/> RL475-RT-BK - Black <input type="checkbox"/> RL475-RT-CH - Chrome <input type="checkbox"/> RL475-RT-CP - Copper <input type="checkbox"/> RL475-RT-SN - Satin Nickel

OPTIONS
<input type="checkbox"/> RL-ACC-SLIM-1-10F - 10ft Long Extension <input type="checkbox"/> RL-ACC-SLIM-1-20F - 20ft Long Extension <input type="checkbox"/> RL-UNV-4/5/6 - Universal Mounting Plate for 4", 5" and 6" <input type="checkbox"/> RL-ACC-SLIM-4-ROUGHPLATE - 4" Mounting Plate <input type="checkbox"/> AL-ACC-SLIM-4-F-ROUGHPLATE - 4" Flanged Roughplate <input type="checkbox"/> EMG-LED-G-16W-HV-FLEX - 16W high voltage inverter ( remote)