



Strobecom OSP Cards

2-Channel Cards:

562/752/762 = [OSPOCV2-2](#) (120VAC cabinets)

562/752/762 = [OSPOCV2DC-2](#) (24VDC cabinets)

*These cards would receive a 10% discount if an old card is traded in (1:1 with no limit)

**OSPOCV2 & OSPOCV2DC cards are backed with a free 10-year warranty

Cut Sheet Link: [OSPOCV2-2](#)

4-Channel Cards:

564/754/764 = [OSPOCV2-4](#) (120VAC cabinets)

564/754/764 = [OSPOCV2DC-4](#) (24VDC cabinets)

*These cards would receive a 10% discount if an old card is traded in (1:1 with no limit)

**OSPOCV2 & OSPOCV2DC cards are backed with a free 10-year warranty

Cut Sheet Link: [OSPOCV2-4](#)

Strobecom Detectors

Single Channel / Single Eye Detectors: (one per approach)

711 = [DETOC1](#)

711 = [DETOC1-IC-x](#) (includes one IC)

*IC style detectors receive a 10% discount if an old detector is traded in (1:1 with no limit)

**X is replaced by W-White/B-Blue

***DETOC series detectors are backed with a free 10-year warranty

Cut Sheets Links: [DETOC1](#) & [DETOC1-IC-x](#)

Single Channel / Two Eye Detectors: (one per approach)

721 = [DETOC21](#)

721 = [DETOC21-1IC-x](#) (includes one IC)

*IC style detectors receive a 10% discount if an old detector is traded in (1:1 with no limit)

**X is replaced by W-White/B-Blue

***DETOC series detectors are backed with a free 10-year warranty

Cut Sheet Links: [DETOC21](#) & [DETOC21-1IC-x](#)

Two Channel w/ Two Detector Eyes: (one detector for two approaches):

722 = [DETOC22](#)

722 = [DETOC22-IC-x](#) (includes two IC's)

*IC style detectors receive a 10% discount if an old detector is traded in (1:1 with no limit)

**X is replaced by W-White/B-Blue

***DETOC series detectors are backed with a free 10-year warranty

Cut Sheet Links: [DETOC22](#) & [DETOC22-IC-x](#)

Strobecom Emitters

T792HL-LOPRO-R (most popular option due to its versatility)

This is a 2"x5"x4" low profile emitter with black metal housing, cable & U-mount universal bracket. This emitter has a (-R) remote power supply which is why this housing is only 4" deep. Making this emitter ideal for installations on a roof, push bar/bumper, in the grill of a vehicle or behind the windshield. Has an approximate range of 2,500 feet. The emitter power supply is backed with a free 10-year warranty.

*Optional [MOTO-VLF](#) (visible light filter)

**Available with Whelen [LOPRO-BKT-WH](#), Federal Signal [LOPRO-BKT-FS](#) or TOMAR [LOPRO-BKT-TM](#) - emitter mounting brackets for light bars.

Cut Sheets: [T792HL-LOPRO-R](#), [LOPRO-BKT-WH](#), [LOPRO-BKT-FS](#) & [LOPRO-BKT-TM](#)

T792HL-LOPRO

This is a 2"x5"x6" low profile self-enclosed emitter with black metal housing, cable & U-mount universal bracket. The power supply is potted inside of the emitter housing which is why this housing is 6" deep. Making this emitter ideal for a nice clean installation on the roof of a fire engine or bucket truck. Has an approximate range of 2,500 feet. The emitter power supply is backed with a free 10-year warranty.

*Optional [MOTO-VLF](#) (visible light filter)

Cut Sheet: [T792HL-LOPRO](#)

T792HL or T792HL-CHROME

This is a standard size 3"x7" self-enclosed emitter with a black or chrome plastic housing, potted power supply & cable. Both are ideal for roof mount installations on a fire engine. Has an approximate range of 2,500 feet. The emitter power supply is backed with a free 10-year warranty.

*Optional [RECT-37-VLF](#) (visible light filter)

Cut Sheet: [T792HL / T792HL-CHROME](#)

T792HL-R

This is a standard size 3"x7" lamp with (-R) remote power supply & cable but no emitter housing or mounting bracket. This kit is ideal for Type 1 ambulances when you mount the lamp to the front of the box. Has an approximate range of 2,500 feet. The emitter power supply is backed with a free 10-year warranty.

*Optional [R37-BZ](#) (chrome bezel), [R37-BZ-B](#) (black bezel), or [RECT-37-VLF](#) (visible light filter)

Cut Sheets: [T792HL-R](#) & [R37-BZ / R37-BZ-B](#)

T792HLB-20V

This is a full power handheld T792HL emitter with DeWalt flashlight handle, DeWalt 20V lithium battery & battery charger. Has an approximate range of 2,500 feet. The emitter power supply is backed with a free 10-year warranty.

*Optional [RECT-37-VLF](#) (visible light filter)

Cut Sheet: [T792HLB-20V](#)

1760-14

This is a low cost & compact handheld tester with a max range of 10 feet.

Cut Sheet: [1760-14](#)

T792HL-R-OML

This is an emitter power supply plus cable which can be paired with an existing strobe lamp.

Cut Sheet: [T792HL-R-OML](#)

Strobeswitch Gate System

2795-2-BCN-AR

This is a dual Strobeswitch assembly and dual color amber/red beacon. Includes two 1790-1014 detectors, one 1790M-2 power module, one dual color beacon & enclosure.

Cut Sheet: [2795-2-BCN-AR](#)

Videos

TOMAR - Driver Response Training Video (Steady/Flash/Off)

<https://vimeo.com/941684852/8611c12926>

TOMAR - Strobecom: New Product Release

<https://vimeo.com/863321294/c48b044831?share=copy>

TOMAR – IC Video

<https://vimeo.com/1159340812/83b28f814a?share=copy&fl=sv&fe=ci>

TOMAR - Strobeswitch: Gate Access

<https://vimeo.com/510902198>

Website

Traffic Division

<https://traffic.tomar.com/>