



ECO 2 FAMILY

WAGO's Eco 2 Power Supplies offer a highly efficient, economical alternative for OEMs and Panel builders. The power supplies are more compact compared WAGO's legacy Eco line while offering higher efficiencies that reduce heat generation and reduce overall energy usage.

Key Features:

- Lever operated connections
- High efficiency
- UL 61010-2-201 and UL HazLoc Class 1 Div 2 approvals
- Wide operating temperatures
- MTBF of >1,000,000 hrs

	2687-2142	2687-2144	2687-2146
Pictures			
Input	1-ph; 90...264 VAC; 50/60Hz		
Output Voltage	24 VDC		
Output Power	30 W	120 W	240 W
Output Current	1.25 A	5 A	10 A
Overload Behavior	Constant Current up to 125%; Shutdown and auto restart in the event of short circuit		Constant Current up to 110%; Shutdown and auto restart in the event of short circuit
Efficiency	88%	90%	93%
Temperature Range	-25...70°C (type-tested -40°C start)		
DC OK LED	Yes		
DC OK Contact	No	Yes	
Overload LED	No	Yes	
Housing	Plastic	Metal	
Dimensions (W x H x D) mm	25 x 100 x 100	38 x 130 x 130	50 x 130 x 130