



APPLICATION and PERFORMANCE SPECIFICATION

Code: 80233

- Line Voltage: 120V 60Hz
- Series Lamp Operation
- Correction
- Rapid Start
- Normal Active Power Factor

Lamp Type			Min. Start Temp. (F/C)	Vin (V)	Iin (A)	Pin (W)	ATHD ≤%	PF ≥	CF ≤	BF	BEF
Type	No.	Watts									
* F32T8	2	32	0/-18	120	0.9	54.3	150	0.5	1.7	0.88	1.59

Note: The above data is tested at 60Hz.

The lamp with "*" is the main lamp.

Application and Performance Specification Information Subject to Change without Notification.

(80233) Electronic Fluorescent Rapid Start 120Volt Ballast works with 1 Lamp or 2 Lamps F32T8, F25T12, F34T12, F20T12, F30T12, F40T12, PL-T32W and other Fluorescent Lamps.

Performance

- Meets Energy Star Version 1.0

Outdoor

- Meets FCC 18 Consumer limits

Application

- Remote Mounting: 18 ft. max. Lead length, 18AWG
- Maximum Ambient Temperature: 104°F, 40°C
- Sound Rated: A
- Maximum case temperature Tc: 167°F, 75°C

Safety

- No PCB's, Type HL
- UL&cUL listed (Class P, Type 1

OCV 600V

Physical Parameters

Length	6"
Width	1.78"
Height	1.08"
Mounting	5.75 "
Weight	0.55 lbs

Lead Length

White, Black	11"(±")
Yellow	38"(±")
Blue/ Red	16"(±")

