

PRODUCT SPECIFICATION SHEET

Deltek Ballast

Watran
Light from the heart



Description: DB2S2232RS120N
Line Voltage: 120-277V / 60Hz Series
Series Lamp Operation
Rapid Start
Normal Power Factor Correction

LampType			Min.Start Temp. (F/C)	Vin (V)	Iin (A)	Pin (W)	ATHD ≤%	PF ≥	CF ≤	BF	BEF	BLE
Type	No.	Watts										
FC12T9	1+1	32	32 ℉/0°C	120	0.58	40	150	0.50	1.7	0.72	1.80	N/A
FC8T9		22										

Performance

MeetsANSIStandardC82.11-2005
MeetsANSIStandardC62.41-2002
Meets FCCPart18consumerlimits

Safety

·NoPCB's,Type HL
UL&cULlisted(Class P,Type1Outdoor)
OCV300V

Application

Remote Mounting: 18ft.max.Leadlength,18AWG
MaximumAmbientTemperature: 167 ℉,75°C
SoundRated: A

PhysicalParameters

Length 6.0"
Width 1.7"
Height 1.1"
Mounting 5.75"
Weight 0.79lbs

LeadLength

White, Black 14"(±1")
Yellow 8"(±1")
Blue,Red 8"(±1")

