

PRODUCT SPECIFICATION SHEET

Deltek Ballast

Watran
Light from the heart



Description: DB2S3240RS120N
Line Voltage: 120V / 60Hz Series
Series Lamp Operation
Rapid Start
Normal Power Factor Correction

LampType			Min.Start Temp. (F/C)	Vin (V)	Iin (A)	Pin (W)	ATHD ≤%	PF ≥	CF ≤	BF	BEF	BLE
Type	No.	Watts										
FC16T9	1+1	40	32 ℉/0°C	120	0.84	58	150	0.50	1.7	0.77	1.33	N/A
FC12T9		32										

Performance

- MeetsANSIStandardC82.11-2005
- MeetsANSIStandardC62.41-2002
- Meets FCCPart18Consumerlimits

Safety

- NoPCB's,Type HL
- UL&cULlisted(Class P,Type 1Outdoor)
- OCV300V

Application

- Remote Mounting: 18ft.max.Leadlength, 18AWG
- MaximumAmbientTemperature: 167 ℉75°C
- SoundRated: A

PhysicalParameters

Length	6.0"
Width	1.7"
Height	1.1"
Mounting	5.75"
Weight	0.79lbs

LeadLength

White, Black	14"(±1")
Yellow	8"(±1")
Blue,Red	8"(±1")

