

SHOEBOX AREA LUMINAIRE

CODE: 90178-45

Project	Information

Type

Name

Voltage

Product Description

LPT shoebox led luminaire has a beautiful low profile design intended for outdoor wall mounted applications, combines the latest in LED technology including weathertight Ip65 LED driver and thermal management. High-performance illumination that lasts 50,000HRS.It's ideal for replacing 500-1000W Metal Halide, with typical energy savings of 80%.



Applications

Parking Lot, Road Ways, Square Parks, Outdoor Lighting Area Lights etc.



Electric Characteristic

Specification/Model		CODE: 90178-45			
LED Chips	SMD 3030	SMD 3030			
Input power	300W	450W 54000-60750 LM 120-135LM/W >70			
Lumens output	37500-42000 LM				
Efficiency	125-140LM/W				
CRI	>70				
Color Temperature 4000K, 4500K, 5000K, 5700K		4000K, 4500K, 5000K, 5700K			
Input voltage	China Brand Driver SS-320V-54B	100-277V Mean Well HLG-240H-48B*2(1-10Vdc Dimmer)			
Beam angle Type III		TypeIII			
Working temperature -20° C TO 45 $^{\circ}$ C		-20°C T0 45°C			
Junction temperature	<75℃	<75℃			
lamps efficiency ≥90%		≥90%			
Certificate	UL	UL 950-1000W MH/HPS			
Equivalent	500-800W MH/HPS				







Product	Power	Replacement	Color Temperature	Photocell	Dimming	Furnish	Head connector
	300W 2 module	500-800W MH/HPS	40K-4000K 45K-4500K	N not photocel	Yes	T-Black Z-Brown	AM DM
CODE: 90178-45	450W 3 module	950-1000W MH/HPS	50K-5000K 57K-5700K	Y yes photocell	163	C-Coffe	YM FM





Photometrics






Projected LED Lumen Maintenance

Operating hours	0	25000	50000
Lumen maintenace factor	1	0.91	0.8

Data references the extrapolated performance projections for the SHOEBOX LED platform in a 25°C ambient, based on 10,000 hours of LED testing (tested per IESNA LM-80-08 and projected per IESNA TM-21-11).

Dimensions



After-sale Service

The product refers to electrics knowledge. Please don't disassemble it by yourself. If any quality problem happens, please contact the factory for warranty details.

NOTE: Actual performance may differ as a result of end-user environment and application. All values are without notice.



