



FROM THE MAKER 



QUICK DRY PENETRATING WOOD FINISH

SPECIFICATIONS

VOC.....	<550 g/L
Solids.....	39% - 45%
Flash Point.....	>100° F
Viscosity.....	20 - 60 cps
Odor.....	Low odor
Coverage.....	500 sq. ft/gal


QUICK DRY
PENETRATING
WOOD FINISH

FEATURES

- Dramatic deep penetrating wood finish
- Stains AND Seals in one-coat application
- Fortified with urethane for long-lasting durability
- Provides a beautiful rich color to most any type wood
- Low odor, non-invasive smell
- Easy to use, glides on smoothly and evenly
- Apply by clean lint free cloth, quality brush or buffer and white pad
- Dries in about 2 hours (varies with conditions and air flow)

PROFESSIONAL WOOD FINISH PENETRATING FINISH FOR ALL HARDWOODS

ABSCO is the #1 choice for high quality floor finishes in wood. Manufactured from the highest quality ingredients available today, QUICK DRY PENETRATING FINISH will provide many years of beauty and deep rich look on all wood floor applications. Colors may be inter-mixed to achieve custom colors. QUICK DRY PENETRATING FINISH is an advanced formulation which can be used with or without a finish coat and is compatible with all Absolute Coatings Group oil-modified and water-borne technologies.

SURFACE PREPARATION: New Wood or Newly Sanded Floors: Prepare the floor according to the NWFA or NOFMA accepted manner. Make several passes with the sandpaper, increasing the paper fineness with each pass. The final pass before application of polyurethane should be with a #100 grit screen disc or sandpaper. Remove dust completely by sweeping, vacuuming, and wiping the floor with a lint free cloth lightly dampened with mineral spirits. The floor, room and product temperature should be at least 65 degrees F.

AVAILABLE IN: Full-range of the most popular colors in quarts and one-gallon containers only.

AbsoluteCoatings.com | OFFICE (732) 821-3200 | FAX (732) 821-8180 | 1999 Elizabeth Street • North Brunswick, NJ 08902