

# R4

Date of printing 10/5/2023

## Technical data

NOTE: The photo shows a general example of the product.

<b>Machine weight, max</b>	22045 - 35275 lb
<b>Max bucket width</b>	63 in
<b>Max breakout force</b>	28100 lbf
<b>Max breakout torque</b>	120225 ft.lb
<b>Weight (from)</b>	838 lb
<b>Tilt angle (2x)</b>	40°
<b>Rotation speed (1 rotation per)</b>	7.0 s at 16 gpm
<b>Working pressure</b>	3626 psi
<b>Max return line pressure</b>	290 psi at 25 gpm
<b>Min hydraulic flow</b>	24.04 gpm
<b>Number of lubrication points</b>	6
<b>Turning torque</b>	5635 ft.lb at 3626 psi
<b>Tilt torque single-acting cylinders</b>	19545 ft.lb
<b>Tilt torque double acting cylinders</b>	28470 ft.lb



## Dimensions

Dimension A, Width	Dimension B, Installation height total	Dimension C, Length	Dimension D, Installation height
28,7 in	40,83 in	27,76 in	19,8 in

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

