

# R2

Date of printing 10/5/2023

## Technical data

NOTE: The photo shows a general example of the product.

<b>Machine weight, max</b>	6614 - 14330 lb
<b>Max bucket width</b>	47 in
<b>Max breakout force</b>	11240 lbf
<b>Max breakout torque</b>	31715 ft.lb
<b>Weight (from)</b>	386 lb
<b>Tilt angle (2x)</b>	40°
<b>Rotation speed (1 rotation per)</b>	7.0 s at 7.9 gpm
<b>Working pressure</b>	3626 psi
<b>Max return line pressure</b>	290 psi at 11 gpm
<b>Min hydraulic flow</b>	11.1 gpm
<b>Number of lubrication points</b>	3
<b>Turning torque</b>	2876 ft.lb at 3626 psi
<b>Tilt torque double acting cylinders</b>	10620 ft.lb



## Dimensions

Dimension A, Width	Dimension B, Installation height total	Dimension C, Length	Dimension D, Installation height
12,36 in	31,89 in	18,43 in	15,31 in

The products in the photos may have additional accessories and features. Technical data and weights may vary depending on the configuration and equipment. We reserve the right to change specifications or designs without prior notice and assume no responsibility for any actual errors that may occur. There may be variations in product programs and equipment standards between the markets. For more information concerning current product specifications, local adaptations and special equipment, please contact your nearest sales office.

