

The ES-C478 Series Electric Strike

ES-C478



The **ES-C478 Series** Electric Strike is designed for use with cylindrical and mortise locksets with up to 3/4" latchbolts. The compact, low profile design with internally mounted solenoid and mounting tabs enable quick and easy installation when jamb space is limited. The heavy-duty construction makes the ES-C478 Series ideal for high traffic installations.

Features:

- For 5/8" latch or 3/4" latch with 1/8" door gap
- Latch position status standard
- Keeper closed & deadlocked / unlocked status standard
- Field selectable voltage, 12/24VAC/DC
- 1/4" horizontal alignment adjustment
- Low profile, 1-1/8" deep
- Plug-in wire connectors
- Mounting tabs
- Non-handed
- All stainless steel parts with durable diecast body for corrosion resistance
- Fewer moving parts for maximum life
- Supplied standard with two square corner faceplates-630/695 finishes
- ANSI A156.31 compliant

Specifications:

	ES-C478
LOCK	
Backset	1-1/8" Low Profile Backset
Dimensions	1.250" (W) x 4.875" (H) x 1.125" (D) {(31.8mm (W) x 124mm (H) x 28.6mm (D)}
Latch	Status Output Standard
Faceplates	1-1/4" x 4-7/8" Two each: 1-square corner 630, 1-square corner 695
Alignment	Horizontal Alignment Adjustment
Finish	630 Dull Stainless Steel & 695 Dark Bronze
ELECTRICAL	
Dual Voltage Coil	280/140mA @ 12/24VDC 170/85mA @ 12/24VAC
Latch Position Status (std)	SPDT, Dry 3Amp @ 30V
Keeper Closed & Locked Status Standard	SPDT, Dry 3Amp @ 30V