

FOR IMMEDIATE RELEASE:

**Laser Time of Flight
Photoelectric Sensors
with IO-Link**



April 2, 2020 - Buffalo Grove, IL - CARLO GAVAZZI is pleased to announce the launch of our new **Photoelectric Laser Sensors with Integrated IO-Link Communications**.

The **LD30 Series** are laser sensors feature great background suppression based on the Time of Flight (ToF) sensing principle. These series of photoelectric sensors have a sensing range of up to 1,000mm for either dark or white objects. The background suppression has been increased four times compared to previous versions. In addition, the **LD30** sensors come in a very compact housing making it ideal for locations with limited space and can be used in an IO-Link network or standard non IO-Link systems. When these sensors are used in an IO-Link network, important data points, like the actual distance to the target can be obtained.

This new family consists of 4 sensor types, in either IP67 plastic (**LD30CNB**) or IP69K stainless steel AISI316L (**LD30ETB**) housings. Furthermore, every sensor can be easily configured in more than half a million combinations through the IO-Link communications, which increases flexibility to solve challenging applications.

The **LD30** sensors have been developed to operate in IO-Link environments, where the sensing performance needs to be monitored and logged. Thanks to the easy and full customization of the sensors, customers can choose from lots of combinations of settings, according to their specific requests. With the launch of these photoelectric sensors with ToF technology and integrated IO-Link functionality, Carlo Gavazzi strengthens their position in the market with a wider product offering.

The LD30 Laser Photoelectric Sensors with IO-Link feature:

- IP69K Stainless steel housing or IP67 Plastic housing
- Two separate switching signal channels (SSC)
- Long range background suppression
- Adjustable sensing distance between 50 to 1000mm via potentiometer or IO-Link
- Modes of operation: Single point, two point and window
- Temperature alarms and logging functions
- Logic gates functionality: AND, OR, X-OR and Gated Set Reset Flip-Flop
- Operating Temperature: -25°C to +50°C (-13° to +122°F)
- Time Delay Functionality: On delay, off delay, one shot leading or trailing edge with values between 1ms to 32,767 minutes
- Two independent outputs fully configurable: NPN/PNP, Push-pull, external input or remote teach NO or NC
- 2 m PVC cable or M8-plug
- IO-Link communication V 1.1

These sensors have been designed to fulfill the industrial requirements and provide accurate detection of objects of different sizes, shapes or surface structures, in the Food & Beverage, Machine Tools, Packaging & Wrapping, Plastic & Rubber, and Material Handling markets.

The **Laser Photoelectric Sensors with IO-Link** are available from Carlo Gavazzi's network of sales offices and distributors in the Americas, or at www.GavazziOnline.com.

Questions regarding this press release should be directed to: Info@CarloGavazzi.com

CARLO GAVAZZI Inc., 750 Hastings Lane, Buffalo Grove, IL 60089
Phone: 847.465.6100 Fax: 800.222.2659 Email: Sales@CarloGavazzi.com

CARLO GAVAZZI (Canada) Inc., 2660 Meadowvale Blvd., Mississauga, ON L5N 6M6
Phone: 888.575.2275 Fax: 905.542.2248 Email: Gavazzi@CarloGavazzi.com

CARLO GAVAZZI Mexico S.A. de C.V., Calle La Montaña no. 28, Fracc. Los Pastores, Naucalpan de Juárez, EDOMEX CP 53340
Phone/Fax: 52.55.5373.7042 Email: MexicoSales@CarloGavazzi.com

CARLO GAVAZZI Automação Ltda., Av. Francisco Matarazzo, 1752 Conj 2018, 05001-200 São Paulo SP
Phone/Fax: 55.11.3052.0832 Email: Info@CarloGavazzi.net.br