

TECHNICAL DATA SHEET

Gemalto Double-sided ID Card Reader CR5400



KEY STANDARD FEATURES & FUNCTIONALITY

- > Double-sided document imaging for ID1 size documents in 24-bit color
- > Configurable image resolution up to 630 DPI
- > Multiple wavelength illumination – visible, near infrared, and UV
- > Anti-Glare technology eliminates image artifacts due to laminate or OVDs
- > Automatic card detection and processing
- > Automatic card eject when reading is complete or when power is turned off
- > Windows® 10 compatible
- > USB 2.0 high speed compatible interface
- > Portrait position when inserting into the ID1 Reader
- > Elegant industrial design look and feel
- > Rugged and durable design
- > Industry standard ¼ x 20 threaded fittings to hold the ID1 Reader to a mounting device (tripod, kiosk, etc.; cradle option only)

Product Use

The Gemalto Double-sided ID Card Reader CR5400 inspects and images government issued identity documents ID1 sized (85 x 54mm) in a variety of market segments like Retail, Financial and Hospitality.

Comprehensive Software Features

- > Flexible software interface allows host application to select which illumination sources to use, image type, image compression, image resolution, photo extraction, reflection or ambient light elimination, color enhancement, which date groups to read
- > Images to be accessed as BMP, PNG or JPEG
- > Simple high level API for quick program development or detailed low level API for fine control of reader functions
- > Contactless IC reading for ePassports (LDS 1.7) including Active and Passive authentication, Basic Access Control, Extended Access Control (PKI 1.11) and Supplemental Access Control. The SDK provides writing capability using APDUs.
- > Full SDK including DLLs, code examples, utilities documentation and demonstration programs. Can be used with Visual C++®, Java®, and Microsoft® .NET Framework for Visual Basic® .NET and Visual C#

Reading Capability

The Gemalto Double-sided ID Card Reader CR5400 reads the following:

- > ICAO compliant ID1 size in near infrared (IR) per ICAO 9303 specification
- > ISO 14443 Type A and B contactless ICs at 13.56 MHz (optional)
- > ISO 7810 and ISO 7811 AAMVA 3-Track Mag
- > 1D barcodes (2 of 5 interleaved, Code 128, and Code 39)
- > 2D barcodes (PDF 417, QR®, DataMatrix™ and Aztec formats)
- > Non ICAO OCR with variable font types and size that displays biographical data found on global government issued IDs (optional)

Illumination

The reader illuminates documents in multiple wavelengths and lighting orientations:

- > Near IR B900, 880nm, +/-5%
- > White visible, 430-700nm
- > Ultraviolet A (UVA): 360-370nm

Resolution

- > Sensor: 10 Megapixels, CMOS, RGB 24 bit color system
- > Configurable image resolution, up to 630 DPI
- > High quality images suitable for reading barcodes and OCR
- > Upgradeable firmware via USB 2.0 interface
- > Non-volatile configuration and calibration accessed via USB 2.0 interface
- > Configuration can be saved to a file for backup or maintenance

Regulatory

- > FCC Part 15 Class A
- > UL, UL-C
- > CE, CB
- > WEEE/RoHS Directive 2011/65/EU

Operating Environment

- > Humidity: 20 to 95% (R.H. non-condensing)
- > Temp: 0° to 40° C operating; -20° to 50° C storage

Standard Dimensions

Imager Only

- > Length: 15.5 cm
- > Width: 10.8 cm
- > Height: 10.2 cm
- > Weight: < 1 kg or 2.2 lbs

Status Indicators

- > The Gemalto Double-sided ID Card Reader CR5400 has an illuminated card slot to enhance ease of use and provide user feedback for optical
- > The readers perform a power-up self-test and indicate failure using status LEDs.
- > Programmable via software SDK

Power

- > USB Powered Imager – USB Powered

Important Notice to Purchaser: Gemalto offers complete solutions and a range of security products to protect against article and/or document identity counterfeit, alteration, diversion, duplication, simulation and substitution. However, no security products can guarantee absolute protection against attempts to successfully accomplish these illegal activities.

Warranty, Limited Remedy and Limited Liability: THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Gemalto warrants that its products will meet Gemalto's written specifications at the time of shipment. Gemalto's obligation and your exclusive remedy shall be, at Gemalto's option, to replace or repair the Gemalto product or refund the purchase price of the Gemalto product. IN NO EVENT WILL GEMALTO BE LIABLE FOR ANY INDIRECT, INCIDENTAL, SPECIAL OR CONSEQUENTIAL DAMAGES INCLUDING, BUT NOT LIMITED TO LOSS OF PROFITS, IN ANY WAY RELATED TO THE PRODUCTS REGARDLESS OF THE LEGAL THEORY ASSERTED. User is responsible for determining whether the Gemalto product is fit for a particular purpose and suitable for user's application. Warranties, remedies and limitations may vary by product and jurisdiction. Please consult Gemalto product quote or agreement, or contact Gemalto for specific information about individual products.

Microsoft, Windows, Vista, Visual C++, Visual C# and Visual Basic are registered trademarks of Microsoft Corporation in the United States and other countries. Java is a registered trademark of Oracle and/or its affiliates. Intel is a trademark of Intel Corporation in the U.S. and/or other countries. Data Matrix is a trademark of Robotic Vision Systems, Inc. (RVSI). QR Code is a registered trademark of DENSO WAVE INCORPORATED. MIFARE and DESFire are trademarks of NXP B.V. All other brand and product names are trademarks or service marks of their respective holders.

© Gemalto 2017. All rights reserved. Gemalto, the Gemalto logo, are trademarks and service marks of Gemalto and are registered in certain countries. Dec 2017 – Jubemo



GEMALTO.COM