



PRECISION MEASUREMENT

3492 Diversified Dr
Loganville, GA 30052
Email: sales@insizeus.com
Phone: 470-240-2520

Connect with us on:



ELECTRONIC CALIPERS (STANDARD MODEL)




1108-150

INSIZE
CERTIFICATE
TRACEABLE TO NIST

DATA
OUTPUT

INSIZE
ISO17025 CERTIFICATE
AVAILABLE AT
EXTRA CHARGE

- Resolution .0005"/0.01mm
- Buttons: on/off, zero, inch/mm
- Automatic power off, move the digital unit to turn on power
- Battery CR2032, data output
- Made of stainless steel
- Optional accessory: data output cable



Part No.	Range	Accuracy	L	a	b	d
1108-150*	0-6"/0-150mm	±.0008"	9.291"	.827"	.630"	1.575"
1108-200*	0-8"/0-200mm	±.0012"	11.260"	.945"	.748"	1.969"
1108-300*	0-12"/0-300mm	±.0012"	15.748"	.984"	.807"	2.362"

*Supplied with manufacturer inspection certificate traceable to NIST

ELECTRONIC WATERPROOF CALIPERS

ATTENTION:
NO DATA OUTPUT




1118-150B

ATTENTION: IT IS NECESSARY TO
SET ZERO AFTER POWER ON EACH TIME

INSIZE
CERTIFICATE
TRACEABLE TO NIST

IP67
WATERPROOF

- Accuracy ±.0012"
- IP67 dust/waterproof
- Resolution .0005"/0.01mm
- Button function: zero, on/off, inch/mm, ABS/REL, hold
- Battery CR2032
- Made of stainless steel



Part No.	Range	L	a	b	c	d
1118-150B*	0-6"/0-150mm	9.291"	.827"	.630"	.630"	1.575"
1118-200B*	0-8"/0-200mm	11.260"	.945"	.748"	.630"	1.969"
1118-300B*	0-12"/0-300mm	15.748"	.984"	.807"	.669"	2.362"

*Supplied with manufacturer inspection certificate traceable to NIST

DIAL CALIPERS

- Shockproof dial indicator
- Made of stainless steel

Dial indicator graduation .001"




1311-6

SHOCK
PROOF

INSIZE
CERTIFICATE
TRACEABLE TO NIST

Part No.	Range	Accuracy	L	a	b	c	d	D	t
1311-6*	0-6"	±.0015"	9.252"	.827"	.650"	.630"	1.575"	1.535" DIA	.256"
1311-8*	0-8"	±.0020"	11.339"	.945"	.748"	.630"	1.890"	1.535" DIA	.256"
1311-12*	0-12"	±.0020"	16.142"	1.102"	.866"	.787"	2.441"	1.752" DIA	.295"


*Supplied with manufacturer inspection certificate traceable to NIST



DEPTH BASE ATTACHMENT



6140



- To increase the stability of depth measurement
- Suitable for digital calipers and dial calipers
- Made of stainless steel

Part No.	Application	b
6140	suitable for calipers with beam width (w) .630"	.354"


ELECTRONIC CALIPER WITH INTERCHANGEABLE POINTS PART NO. 1526-200




1526-200

DATA
OUTPUT

- Supplied with 3 pairs of points and zero setting block for external measurement
- Resolution .0005"/0.01mm
- Buttons: on/off, set, inch/mm, preset (+, -)
- Automatic power off, move the digital unit to turn on power
- Battery CR2032, data output
- Made of stainless steel
- Optional accessory: points, depth stop, data output cable



depth stop 6143
(optional)



Part No.
1526-200


short spherical points (included)



long spherical/flat points (included)



spherical blade points (included)



Point	Range	Accuracy	Application
short spherical points	.5-8.5"/12-212mm (internal)	±.0012"	for grooves inside small hole
long spherical/flat points	1-8.8"/24-224mm (internal) 0-7.5"/0-187mm (external)	±.0012"	spherical points for grooves inside hole flat points for external grooves
spherical blade points	1-8.8"/24-224mm (internal) 0-7.5"/0-187mm (external)	±.0012"	for narrow grooves inside hole