


halolighting.com

September 22, 2020

HALO® Fire Safe 2-Hour Fire Rated Housings

HALO is pleased to announce the addition of the 3-inch Fire Safe Housings to the 4-inch and 6-inch product family. These housings are compatible with 3" HALO LED recessed modules and are rated to prevent the passage of flames and toxic gases for up to 2 hours in accordance to UL 263, with the added benefit of no additional installation time. HALO Fire Safe Housings are an affordable option to provide.

Features at a Glance

- 3-inch new construction LED housings
- Prevents the passage of flames and toxic gases for up to 2 hours in accordance to UL 263
- No need to build additional boxes anymore
- Air-tite and suitable for direct contact with insulation
- Five-year limited warranty

Compatible with the following HALO LED modules

- RL3
- RA3



Catalog Number	Material Number	Description	UPC
H350FR2ICAT	13393480	3" 2H Fire Rated, ICAT, 10W LED	080083130481

Selling Tools

Specification sheets and installation instructions are available now, refer to the HALO Recessed website. Consult FLASH for pricing and availability. Take advantage of this exciting new product introduction and grow your HALO Recessed sales now.

See HALO in a whole new light!

Glenn Siegel

Marketing & Product
Management Director

Bryant Bilal

Product & Marketing Manager
HALO Recessed

Joseph DiPietro

Product & Marketing Manager
HALO Recessed



Cooper Lighting Solutions is a registered trademark.

All other trademarks are property of their respective owners.

Product availability, specifications, and compliances are subject to change without notice.