

CHLORIDE

by (s)ignify

Compac

Exit & emergency family



Small in scale,
impressive in styling and performance

Emergency lighting that actually fits into your carefully designed spaces

Chloride Compac LED exit / emergency family
has been designed to fit every aspect of your
commercial and light industrial applications.



And here's how:

- Fits into aesthetically demanding areas with its low profile and is complimentary of the environment in which it is installed.
- Fits neatly into your specification process because we have each type of emergency product that most commercial and industrial applications need.
- Fits into light industrial spaces with the appropriate damp location ratings and local safety codes.*
- Fits easily into your customer's project budget by saving in annual maintenance costs with standard self-testing/self-diagnostics and in lower energy consumption with LED sources.

*Consult product spec sheets for specific rating and code information.



Emergency lighting the only products you hope you will never need.

But, when you do need them, you want to know they will be ready to guide you to safety. Trust the Chloride Compac LED exit and emergency family for piece of mind during an emergency.

And, these are the reasons why:

Compac exit/emergency products are reliable because they come standard with monthly self-testing and self-diagnostics ensuring they are ready when they are needed most.

They are well designed because the housings are constructed of rugged thermoplastic to meet your expectations of high quality products.

They are high performers because the lamps put the light where it needs to be while also requiring fewer units to be installed compared to traditional lamp sources. Fewer units equals less cost to your project budget.

They look good in commercial spaces because their low profiles allow them to blend beautifully into the background, but are visible when you need them.

Perfect planning with

Compac LED

Exits, combos, emergency units, and remote lamp heads should all be a part of a carefully laid out emergency plan. The Chloride Compac LED emergency lighting family is designed to be the perfect solution to that plan.



Chloride Compac LED exit sign CLX

is the basic workhorse emergency product within a space. It provides brightly lit uniform letters for locating points of egress.



Chloride Compac LED emergency exit/unit combo CLC

is designed as two products in one. So, this product combines the benefits of high performance emergency lighting and the features of an exit for safe egress.



Chloride Compac LED recessed CLUR3

has an excellent low-profile and is designed to be installed into grid ceilings and drywall installations.

All units have a profile that is
less than 3 inches

Specifying a job just got easier,
keep a cohesive look and feel with one complete
exit/emergency family.



Chloride Compac LED emergency unit CLU and CLU2/CLU3

are small to mid-sized emergency units designed for high performance providing excellent emergency illumination on the path of egress.

Chloride Compac LED remote head CLR

was designed with the beautiful styling and high performance found in the rest of the Compac LED family.



Chloride Compac LED exit sign CLX

is designed with a low-profile that is a welcome alternative to typically bulky exit signs. It comes with self-diagnostics/self test circuitry standard which provides significant maintenance savings.



Chloride Compac LED emergency exit/unit combo CLC

has been designed to be the essential emergency product in the most common applications. It includes every day directional guidance to points of egress and illuminates the way in an emergency situation. Standard self-diagnostics and self-test circuitry provide significant maintenance efficiencies and higher lumen output means wider coverage from a single exit/unit combo.

Performance

	80/50/20 Reflectance [†]		10/10/10 Reflectance [‡]	
	3' Path	6' Path	3' Path	6' Path
Center-to center spacing	58'	56'		
Single Coverage	57'	55'	48'	42'

[†]Based on 6ft corridor and 9ft ceiling height and a mounting height of 7.5ft.

[‡]Based on 200ft by 200ft open area and 30ft ceiling height.



Key Features:

- 2-1/8" profile specifically designed around LED technology
- Lightweight construction for hassle-free installation: CLX 3.45lbs / CLC 4.15lbs.
- The CLC has flush mounted adjustable LED lamp heads provide linear and forward throw illumination. They can also be mounted on the opposite side of the face plate for back lighting purposes if needed
- Compact Nickel Metal Hydride battery
- All Compac LED products with a battery are standard with Self-diagnostic / Self-test feature
- Suitable for both commercial and light industrial applications
- CLX and CLC exit/unit combo is ETL Listed per UL 924 Standard for dry/damp locations
- Meets the NFPA 70 (National Electric Code), NFPA 101 (Life Safety Code), and the California Energy Commission



Key Features:

- 2-5/8" profile specifically designed around LED technology
- 2.05 lbs lightweight construction for hassle-free installation
- Flame rated, UV stable thermoplastic housing
- Compact nickel metal hydride battery
- Standard Self-diagnostic / Self-test electronics
- Suitable for both commercial and light industrial applications
- Snap-together quick mount design for quick and easy installation
- CLU2 / CLU3 units are ETL Listed per UL 924 Standard for dry / damp locations
- Meets the NFPA 70 (National Electric Code), NFPA 101 (Life Safety Code), and the California Energy Commission

Chloride Compac LED emergency unit CLU2/3

is offered in both two lamp and three lamps versions. The two lamp offering provides fully adjustable lamps for your directional needs. The three lamp version has a fixed center lamp that fills in the center and allows the two adjustable heads to angle out even further.

CLU2



CLU3



Performance

	80/50/20 Reflectance [†]		10/10/10 Reflectance [‡]	
Center-to center spacing	3' Path	6' Path	3' Path	6' Path
CLU2 Unit	58'	55'	48'	54'
CLU3 Unit	72'	72'	62'	42'
Single Coverage	3' Path	6' Path	3' Path	6' Path
CLU2 Unit	58'	54'	48'	42'
CLU3 Unit	68'	68'	62'	54'

[†]Based on 6ft corridor and 9ft ceiling height and a mounting height of 7.5ft.

[‡]Based on 200ft by 200ft open area and 30ft ceiling height.

Chloride Compac LED emergency unit CLU

Don't let it's small size fool you. The CLU was designed to fit into small and unobtrusive areas, but also deliver the optimum performance in treacherous situations. The two high-output lamps are fully aimable to the necessary angle.



Performance

80/50/20 Reflectance [†]		
	3' Path	6' Path
Center-to center spacing	40'	35'

[†]Based on 6ft corridor and 9ft ceiling height and a mounting height of 7.5ft.

Key Features:

- 2-5/8" profile specifically designed around LED technology
- 1.1lbs. lightweight construction for hassle-free installation
- Flame rated, UV stable thermoplastic housing
- Compact Nickel Cadmium battery
- Standard Self-diagnostic / Self-test electronics
- Suitable for both commercial and light industrial applications
- Snap-together quick mount design for quick and easy installation into walls or ceilings
- CLU emergency unit is ETL Listed per UL 924 Standard for dry/damp locations
- Meets the NFPA 70 (National Electric Code), and NFPA 101 (Life Safety Code) and the California Energy Commission

Chloride Compac LED recessed emergency unit CLUR3

features styling to match the rest of the Compac family for continuity, but conveniently stays out of the line of sight in the ceiling or if mounted in the wall. Of course, it is right there when it is needed in an emergency. This unit comes standard with two fully adjustable heads and one fixed center head providing the light distribution where needed for the path of egress.



Performance

80/50/20 Reflectance		
	3' Path	6' Path
Center-to-center spacing	70'	70'
Single coverage	64'	64'

Mounting height is 10ft, Unit mounted to ceiling.
80/50/20 reflectance based on 6ft corridor.

Key Features:

- 4.9 lbs lightweight construction for hassle-free installation
- Flame rated, UV stable thermoplastic housing
- Compact nickel metal hydride battery
- Standard Self-diagnostic / Self-test electronics
- Suitable for both commercial and light industrial applications
- Snap-together quick mount design for quick and easy installation
- CLUR3 emergency unit is ETL Listed per UL 924 Standard for dry/damp locations
- Meets the NFPA 70 (National Electric Code), NFPA 101 (Life Safety Code), and the California Energy Commission

Chloride Compac LED remote unit CLR

features complementary styling to match the rest of the Compac family and adds to the appeal of the complete product offering. It is also small, but packs a big punch on performance.



CLR



CLR
wet location

Performance

Center-to-Center Spacing	80/50/20 Reflectance [†]		10/10/10 Reflectance [‡]	
	3' Path	6' Path	3' Path	6' Path
CLR Two remote lamp head	58'	56'	48'	42'

[†]Based on 6ft corridor and 9ft ceiling height and a mounting height of 7.5ft.

[‡]Based on 200ft by 200ft open area and 30ft ceiling height.

Key Features:

- 2-5/8" profile specifically designed around LED technology
- 0.8 lb lightweight construction for hassle-free installation
- Flame rated, UV stable thermoplastic housing
- Suitable for both commercial and light industrial applications
- Snap-together quick mount design for quick and easy installation
- 1 or 2 lamp CLR is suitable for damp locations and 2 lamp CLR **with gasketing** is suitable for wet locations
- Meets the NFPA 70 (National Electric Code), NFPA 101 (Life Safety Code), and the California Energy Commission



Take the next step

Easily integrate Chloride Compac LED emergency units and exits into every aspect of your commercial/industrial applications.

Visit chloride-lighting.com





© 2019 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

PCh-1804BR_Compac_brochure 02/19 www.chloride-lighting.com

Signify North America Corporation
200 Franklin Square Drive,
Somerset, NJ 08873
Telephone 855-486-2216

Signify Canada Ltd.
281 Hillmount Road,
Markham, ON, Canada L6C 2S3
Telephone 800-668-9008