


TH5-19

TH



GEHL[®]

Capacities		Metric		Imperial
Max. capacity		2494.75 kg		5500 lb
Max. lifting height		5.82 m		19 ft 1 in
Max. outreach		3.40 m		11 ft 2 in
Breakout force with bucket		3425.13 daN		3425.13 daN
Weight and dimensions				
Length to face of forks	l2	3.89 m		12 ft 9 in
Overall width	b1	1.81 m		5 ft 11 in
Overall height	h17	1.92 m		6 ft 4 in
Wheelbase	y	2300 mm		91 in
Ground clearance	m4	330 mm		13 in
Overall cab width	b4	797 mm		31 in
Tilt-up angle	a4	12 °		12 °
Tilt-down angle	a5	117 °		117 °
External turning radius (over tyres)	Wa1	3.31 m		10 ft 10 in
Unladen weight (with forks)		4720 kg		10406 lb
Tires type		Pneumatic		Pneumatic
Forks length / width / section	l / e / s	1200 mm x 125 mm / 45 mm		47 in x 5 in / 2 in
Performances				
Lifting		8 s		8 s
Lowering		5.40 s		5.40 s
Extension		5.60 s		5.60 s
Retraction		4.30 s		4.30 s
Crown		3.50 s		3.50 s
Dump		3.60 s		3.60 s
Engine				
Engine brand		Kubota		Kubota
Engine norm		Tier 4 final		Tier 4 final
Engine model		V3307-CR-TE5B		V3307-CR-TE5B
Number of cylinders / Capacity of cylinders		4 - 3331 cm ³		4 - 203 in ³
I.C. Engine power rating - Power (kW)		74 Hp / 55.40 kW		74 Hp / 55.40 kW
Max. torque / Engine rotation		1400 Nm @ 2600 rpm		1033 ft/lbs @ 2600 rpm
Drawbar pull		3229.40 daN		3229.40 daN
Electric circuit				
12V Battery capacity		110 Ah		110 Ah
Transmission				
Transmission type		Hydrostatic		Hydrostatic
Number of gears (forward / reverse)		2 / 2		2 / 2
Max. travel speed		25 km/h		16 mph
Parking brake		Oil immersed multi-discs braking on front axle type SAHR brake		Oil immersed multi-discs braking on front axle type SAHR brake
Service brake		Oil-immersed multi-discs braking on front axles		Oil-Immersed multi-discs braking on front axles
Hydraulics				
Hydraulic pump type		Gear pump		Gear pump
Hydraulic flow / Pressure		88 l/min-235 bar		23 US gpm-3408 PSI
Tank capacities				
Engine oil		11.20 l		3 US gal
Hydraulic oil		115 l		30 US gal
Fuel tank		63 l		17 US gal
Miscellaneous				
Steering wheels (front / rear)		2 / 2		2 / 2
Drive wheels (front / rear)		2 / 2		2 / 2
Controls		Joystick		Joystick



GEHL®

Siège Social
P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095
Tel: (262) 334-9461 - Fax: (262) 338-7517
www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend