



S-1316AH SHUR-LOC® Handle Eye Hook

www.thecrosbygroup.com

GET A GRIP ON YOUR LOAD

The SHUR-LOC® Handle Eye Hook gives you better control of your load without compromising the operator's safety. The new ergonomic handle is roomy enough for use with almost any size gloved hand for complete control over the hook and load. Made with forged alloy steel, the hook is suitable for use with Grade 100 or Grade 80 chain.



S-1316AH SHUR-LOC® Handle Eye Hook

The handle hilt provides added protection of user's hand

Positive lock latch is self-locking when hook is loaded

Replaceable pull-trigger for easy operation of the positive self-lock latch

The SHUR-LOC® Handle Eye Hook allows the user to get a confident grip on any load. Handle opening big enough to accommodate a gloved hand

Recessed trigger design better protects the trigger from potential damage

S-1316AH SHUR-LOC® Handle Eye Hook

Chain Size		Working Load Limit 4:1	Working Load Limit 5:1	Frame Code	Weight Each	Stock Number
(in.)	(mm)					
5/8	16	22,600 (lbs) 10.3 (t)	18,080 (lbs) 8.2 (t)	JA	18 (lbs) 8.2 (kgs)	1023579
3/4	18/20	35,300 (lbs) 16.0 (t)	28,240 (lbs) 12.8 (t)	KA	28 (lbs) 12.7 (kgs)	1023599
7/8	22	42,700 (lbs) 19.4 (t)	34,160 (lbs) 15.5 (t)	LA	39 (lbs) 17.7 (kgs)	1023607
1	26	59,700 (lbs) 27.1 (t)	47,760 (lbs) 21.7 (t)	NA	60 (lbs) 27.2 (kgs)	1023625



S-13326AH SHUR-LOC® Handle Swivel Hook with Bearing

www.thecrosbygroup.com

MORE CONTROL WITH SMOOTHER OPERATIONS

- Bearing lubricated with long-lasting lithium-based grease
- Bearing gives better control over load
- The SHUR-LOC® handle hook allows the user to get a confident grip on any load
- Handle opening big enough to accommodate a gloved hand
- Replaceable pull-trigger for easy operation of the positive self-lock latch

Low friction bearing for better positioning load when lifted

Positive lock latch is self-locking when hook is loaded

Handle hilt provides added protection of user's hand

*Recessed trigger design better protects the trigger
from potential damage*



S-13326AH SHUR-LOC® HANDLE SWIVEL HOOK with Bearing

S-13326AH SHUR-LOC Handle Swivel Hook with Bearing						
Chain Size		Working Load Limit 4:1	Working Load Limit 5:1	Frame Code	Weight Each	Stock Number
(in.)	(mm)					
5/8	16	22,600 (lbs) 10.3 (t)	18,080 (lbs) 8.2 (t)	JA	26 (lbs) 11.8 (kgs)	1005014
3/4	18/20	35,300 (lbs) 16.0 (t)	28,240 (lbs) 12.8 (t)	KA	37 (lbs) 16.8 (kgs)	1005023
7/8	22	42,700 (lbs) 19.4 (t)	34,160 (lbs) 15.5 (t)	LA	57 (lbs) 25.9 (kgs)	1005041
1	26	59,700 (lbs) 27.1 (t)	47,760 (lbs) 21.7 (t)	NA	84 (lbs) 38.1 (kgs)	1005050

9992485 1/18/17

Crosby® 8/10™



Fatigue Rated®