

TEMPORARY GUI DOWNLOADS DURING WEBSITE TRANSITION

Latest EVO - GUI Software

[EVO - GUI Software Rev V0.0.0.53](#)

[EVO - GUI User manual](#)

Standard GUI Software (National Instruments - LabView)

NOTE 1: SBS2 and Beacon Receiver products require GUI v4.0 or newer

NOTE 2: The [sbs2net](#) tool to help set SBS2 IP Address should no longer be needed when using GUI V4.0rc59 or later

August 21, 2019 - GUI v4.0rc59 pre-release update available!

⇒ Any previous v4.0 version should be replaced with v4.0rc59

Downloads for Windows XP and greater.

If you have previously installed an Avcom GUI, then you have the necessary drivers and can save time by downloading the Lite version which is a GUI update only. These are zipped (.zip) installers. Save to local drive then unzip to install.

Save file to local drive then double-click to install.

System Requirements for Windows GUIs: Windows XP and greater

CPU: Pentium III 1.5GHz or equivalent (Pentium 4/M or equivalent recommended)

Memory: Depends on # Windows shown. 3GB RAM for 12 Windows

Changes: Issue Fixed: Incorrect marker frequencies. Additional Beacon Receiver settings and features.

v4.0rc59 GUI includes SBS2 support

[Windows GUI v4.0rc59 FULL](#)

(153MB)

v4.0rc59 GUI includes SBS2 support

GUI for Windows only and drivers, FTDI USB drivers, and Net-SNMP installer

[Windows GUI v4.0rc59 LITE](#)

(11MB)

v4.0rc59 GUI includes SBS2 support

April 17, 2013 - Standard GUI v3.0.2 Released!

Downloads for Windows 2000 (SP3) and greater.

No SBS2 or Beacon Receiver support

Standard GUI

The Standard GUI is what is shipped on CD with all of our analyzers. If you have already downloaded the Full version then you have the necessary drivers and can save time by downloading the Lite version which is a GUI update only.

These are zipped (.zip) installers. Save to local drive then unzip to install.

System Requirements for Windows GUIs: Windows 2000(SP3) and greater

CPU: Pentium III 1.5GHz or equivalent (Pentium 4/M or equivalent recommended)

Memory: Depends on # Windows shown. 3GB RAM for 12 Windows

[Windows GUI v3.0.2 FULL](#)

(130MB)

v3.0.2 GUI for Windows only and drivers, FTDI USB drivers, and Net-SNMP installer

[Windows GUI v3.0.2 LITE](#)

(10MB)

v3.0.2 GUI for Windows only. No drivers for GUI or SNMP.