



Bluetooth Controlled Integrated Dual Occupancy and Daylight Sensor



### JSTR-CT/DSP LINEAR CCT & POWER SELECTABLE LED STAIRWELL STRIP SERIES

#### Product Features

- Input Power:**
  - 2' from 10W to 30W
  - 4' from 12W to 40W
  - 8' from 45W to 80W
- Average Efficacy:** 135Lm/W Max
- Input Voltage:** 120-277VAC or 100-347VAC
- CCT Options:**
  - Static 3000K/ 4000K/ 5000K
  - CCT Selectable (3000K / 4000K / 5000K)
- CRI:** >80
- Sensors:**
  - BMW-RC Integrated Microwave Bi-level Occupancy sensor with Remote Control
  - BMW-DP Bi-level Built-In Microwave Occupancy Sensor with Dip Switch.
- Mounting:**
  - Surface
  - Pendant
- Lifetime Based on TM21:** L70 @ ≥ 147,000 hrs/ L80 @ ≥ 108,000 hrs/ L90 @ ≥ 61,000 hrs
- Certifications & Compliance:** DLC Premium, FCC, UL or ETL
- Warranty:** 10 years limited warranty

[CLICK HERE FOR WEBPAGE](#)



Bluetooth Controlled Integrated Dual Occupancy and Daylight Sensor



### JPTR VOLUMETRIC ARCHITECTURAL CCT & POWER SELECTABLE INTELLIGENT TROFFER SERIES

#### Product Features

- Input Power:**
  - 1' x 4' in 36W/ 40W
  - 2' x 2' from 26W/ 30W/ 32W/ 36W
  - 2' x 4' from 32W/ 40W/ 45W/ 50W
- Average Efficacy:** 125Lm/W to 145Lm/W (HE Series)
- Input Voltage:** 120-277VAC or 100-347VAC
- CCT Options:**
  - Static 3000K/ 3500K/ 4000K/ 5000K
  - CCT Selectable (3500K/ 4000K/ 5000K)
- CRI:** >80 or >90 Optional
- Sensors:**
  - BMW-RC Integrated Microwave Bi-level Occupancy sensor with Remote Control
  - JICS-BT-SC Single Channel Bluetooth Indoor Controls System
- Mounting:**
  - Surface
  - Pendant
- Lifetime Based on TM21:** L70 @ 206,000 Hrs/ L80 @ 130,000 Hrs/ L90 @ 63,000 Hrs
- Certifications & Compliance:** DLC Premium, FCC, UL or ETL, IC Rated
- Warranty:** 10 years limited warranty

[CLICK HERE FOR WEBPAGE](#)



Bluetooth Controlled Integrated Dual Occupancy and Daylight Sensor



### JFP-BL-CPS SERIES BACK-LIT CCT & POWER SELECTABLE FLAT PANEL TROFFER SERIES

#### Product Features

- Input Power:**
  - 1' x 4' 40W Model (20W/ 30W/ 40W)
  - 2' x 2' 36W Model (20W/ 30W/ 36W)
  - 2' x 4' 45W Model (30W/ 40W/ 45W)
- Average Efficacy:** 126Lm/W on average
- Input Voltage:** 100-277VAC or 100-480VAC
- CCT Options:**
  - Static 3500K/ 4000K/ 5000K
  - CCT Selectable (3500K/ 4000K/ 5000K)
- CRI:** >80
- Sensors:**
  - BMW-RC Integrated Microwave Bi-level Occupancy sensor with Remote Control
- Mounting:**
  - Surface
  - Pendant
  - Recessed T-bar Grid Ceiling
- Lifetime Based on TM21:** L70 @ 183,000Hrs/ L80 @ 143,000Hrs/ L90 @ 121,000Hrs
- Certifications & Compliance:** DLC Premium, FCC, UL or ETL, IC Rated
- Warranty:** 10 years limited warranty

[CLICK HERE FOR WEBPAGE](#)

