



Flav-R 2-Go® Locker System - Floor Mount

Models: F2G-24-A, -34-A
F2G-24-C, -34-C

The Hatco Flav-R 2-Go® Locker System - Floor Mount, designed specifically for your pick-up and third-party delivery needs, is capable of holding multiple orders of hot or ambient food with quick and secure access. By reducing congestion and allowing employees to focus on other functions, customers or delivery people can arrive, access their specific locker, and leave without waiting in line or disturbing the flow of other business.

Standard features

- Counter top and built-in models also available, see alternate spec sheets
- Each locker unit has a large 10" (254 mm) touchscreen on the operator side and on the customer side. The operator puts in the name and code. The customer receives the code, enters it on the customer side, and the appropriate door unlocks and LED lights flash
- F2G-34 has customer facing controls on the left side of the unit. Operator controls will be on the right-hand side. Reverse control locations are available as an option.
- F2G-24 has customer facing controls in the center of the unit. Operator controls will be the same
- Each locker has a timer that will hold prepared and packaged food for up to 45 minutes
- Lockers come preset to 150°F (66°C) but can be adjusted up to 180°F (82°C)
- Individual lockers can have the heat turned off for ambient storage
- Internal lockers come standard in Gloss Smooth White with LED indicator lights that can be programmed to six different colors: blue (standard), red, green, yellow, magenta or white (all lockers will be one color)
- Manual (standard) or POS integration capabilities available (outside vendor required)
- Available with pass-through or optional Back Panels create a one-sided access with the touchscreen only on the customer side. Available in two locker depth sizes, *Designer* colors and the ability to have a custom logo on the customer side glass doors

Project _____

Item # _____

Quantity _____



Options (available at time of purchase only)

Designer Colors -

Non-standard colors are non-returnable – Warm Red standard

Black Gray Granite White Granite
 Navy Blue Hunter Green Antique Copper

Right Side Control Panel on customer side (in lieu of left side control panel) – operator control panel would switch to left side (in lieu of right side control panel) – F2G-34 model only –

Back panels – Creates a non-pass-through unit – (The power switch will move beside cord location) (subtract .58" [14 mm] to the depth) – Non-pass-through units have control panel only on customer side –

Cord location: Side of unit, facing operator side, right side of unit, bottom corner closest to operator side – in lieu of standard: facing operator side, left side of unit, bottom corner closest to operator side –

QR Code Reader –

For non-pass-through units only. Must be combined with Back Panels
 For pass-through units only

Accessories

Wall Mount Bracket (mounting hardware not included)

 **IFS** anti-microbial coatings use naturally-occurring, environmentally sustainable, silver ions to help inhibit the growth of microbes on the powder coated surface. See www.hatcocorp.com/antimicrobial-paint for more information.

 For operation, location and safety information, please refer to the Installation and Operating Manual.



MADE IN
THE USA

HATCO CORPORATION | P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. | (800) 558-0607 | (414) 671-6350


 www.hatcocorp.com | support@hatcocorp.com | [Find a Hatco Rep](#) | [Image Library](#) | [Document Library](#) | [Chat](#)




Flav-R 2-Go® Locker System - Floor Mount

Models: F2G-24-A, -34-A F2G-24-C, -34-C

F2G-24



F2G-34



SPECIFICATIONS

Flav-R 2-Go® Locker Systems - Floor Mount

Model	Model Dimensions (W x D x H)	Number of Lockers	Internal Locker Dimensions	Volts	Watts	Amps	Plug
F2G-24-A	45.34" x 14.27" x 71.24" (1152 x 362 x 1809 mm)	8 lockers	12" x 12" x 12" (305 x 305 x 305 mm)	120	831	7.3	NEMA 5-15P
F2G-24-C	45.34" x 22.77" x 71.24" (1152 x 578 x 1809 mm)	8 lockers	12" x 20.5" x 12" (305 x 521 x 305 mm)	120	1087	9.4	NEMA 5-15P
F2G-34-A	62.14" x 14.27" x 71.24" (1578 x 362 x 1809 mm)	12 lockers	12" x 12" x 12" (305 x 305 x 305 mm)	120	1239	10.8	NEMA 5-15P
F2G-34-C	62.14" x 22.77" x 71.24" (1578 x 578 x 1809 mm)	12 lockers	12" x 20.5" x 12" (305 x 521 x 305 mm)	120	1623	14.0	NEMA 5-15P [▲]


▲ Canadian models use NEMA 5-20P.

CORD LOCATION

Facing operator side, left side of unit, bottom corner closest to operator side.

PLUG CONFIGURATIONS

NEMA 5-15P



NEMA 5-20P



PRODUCT SPECS

Flav-R 2-Go® Locker System

The Locker System shall be a Flav-R 2-Go® Model ... , rated at ... volts, and ... watts, by the Hatco Corporation, Milwaukee, WI 53234 U.S.A.

The lockers shall consist of magnetically locked hinged doors, heated base, a 10"

(254 mm) touchscreen controller on one or both sides of the unit, a Power on/off switch, LED lighting and a 6' (1829 mm) cord with plug attached.

Warranty consists of 24/7 parts and service assistance (U.S. and Canada only).

