

Cleaning Recommendations

Cleaning of PVC Laminates

Avery Dennison films should not be cleaned or washed within the first 48 hours after application.

For cleaning of exterior floor graphics, the high-pressure equipment should not exceed 1200 psi (80 bars or 84 kg/cm²). A minimum distance of 12 inches should be maintained to prevent decal edge lift. Use a nozzle with a 40 degree angle wide spray pattern.

Wear appropriate PPE (Personal Protective Equipment). For more information, please check your local government health guidelines.

These cleaning products are recommended for use

Detergent / solutions: ie dishwashing liquids	✓
Detergent disinfection / disinfectants (chlorine-based) / antibacterial surface wipes - sprays	✓
Bleach (must be diluted following the instructions Of the manufacturer)	✓
Cleaner pH should be between 5 and 9	

These cleaning products are not recommended for use

Solvents	✗
Powder or liquid abrasive cleaners	✗
Scourers	✗
Harsh chemicals e.g. acids, alkali solutions	✗

Frequently touched surfaces

- Door handles, bedrails, tabletops, light switches
- ★ Should be frequently, mechanically cleaned.
- ★ Detergent solution (as per manufacturer's instructions) or detergent/disinfectant wipes can be used (so long as mechanical cleaning is achieved).

Routine Environmental Cleaning

Minimally touched surfaces

- Floors, ceilings, walls, blinds
- ★ Detergent solution/wipes (as per manufacturer's instructions) are adequate for cleaning general surfaces and non-patient care areas.
- ★ Damp mopping is preferable to dry mopping dry mopping.
- ★ Walls and blind should be cleaned when visibly dusty or soiled.
- ★ Window curtains should be regularly changed in addition to be cleaned when soiled.
- Sinks and basins should be cleaned on a regular basis.